


TIMING PULLEYS
時規皮帶輪
- 2GT -




齒形




型號	皮帶寬度	材質		表面處理
		皮帶輪	擋片	
KAL	GT2-4 GT2-6 GT2-9	A6061	A6061	白色陽極處理

皮帶輪形狀

AF形




BF形




軸孔形狀


□圓孔



□圓孔+攻牙



□新JIS鍍槽孔+攻牙



dH7	M	T·N 止付螺絲(附屬品)
5	M3	M3X3 2支
6~22	M4	M4X3 2支

型號	齒數	皮帶寬度	形狀	皮帶輪尺寸												軸孔規格								
				2GT-4			2GT-6			2GT-9			S		T		N							
				P.D.	O.D.	D	F	E	A	W	L	A	W	L	A	W	L	dH7						
																AF	BF	AF	BF	AF	BF			
KAL	14	GT2-4	AF	8.91	8.40	—	13	6	5	8.3	—	7	10.3	—	10	13.3	—	3	—	—	—	—	—	
	15			9.55	9.04	—	14	7										3·4						
	16			10.19	9.68	—	14	7										3·4						
	18			11.46	10.95	—	16	8										4						
	20			12.73	12.22	—	17	9										4·4.5·5						
	21			13.37	12.86	—	18	10										4~6						
	22			14.01	13.50	8	18	10										4~6						4
	24			15.28	14.77	10	20	12										5~8						5·6
	25			15.92	15.41	10	20	12										5~8						5~7
	26			16.55	16.04	10	21	12										5~8						5~8
	28	17.83	17.32	10	23	14	5~10	5~8	5	8.3	16	7	10.3	18	10	13.3	21	6~14	6~10	6~10	6~8	—		
	30	19.10	18.59	11	24	15	5~11	5~8										6~14	6~10	6~10	6~8			
	32	20.37	19.86	13	25	17	5~13	5~9										5~10	5·6	—				
	34	21.65	21.14	14	27	18	6~14	6~10										6~10	6~8					
	36	22.92	22.41	14	27	18	6~14	6~10										6~10	6~8					
	38	24.19	23.68	16	29	20	6~16	6~12										6~10	6~8		8			
	40	25.46	24.95	17	30	21	6~17	6~13										6~12	6~10		8·10			
	44	28.01	27.50	19	32	23	6~19	6~15										6~13	6~12		8~11			
	48	30.56	30.05	22	35	26	8~22	8~18										8~15	8~12		8~13		8	
	50	31.83	31.32	22	36	27	8~23	8~18										8~16	8~12		8~14		8	
60	38.20	37.69	28	42	33	8~29	8~24	8~22	8~22	8~19	8~14													

轉造級滾珠螺桿

螺桿支撐座

聯軸器

時規皮帶輪